

ALPHA BRIDGE - Unmanaged 8 Port PoE Switch

Product Overview

The PoE switch provides power and data from a single point, using Power over Ethernet (PoE) over a single Cat-5 cable. It can be used for any 10/100/1000Mbps link and supply industry-standard IEEE 802.3af/at power. Advanced auto-sensing algorithm gives power to 802.3af/at end devices. In addition, the PoE switch automatically determines PoE requirements, speed, duplex, and cable type using Auto Uplink. Easy to operate and reliable. The PoE switch is ideal for powering PoE devices such as IP cameras, WLAN access point, IP phones, office access control systems, and other PD devices and offers a line of high-quality products that provide a total solution for Ethernet application in different environments.

Product Characteristics

- If uplink is RJ45 port: 100m transmission distance, 250m after use extend function; If uplink is fiber port, max. transmission distance is 120km.
- IEEE 802.3af/at power on POE ports
- Supply power to wireless access points and surveillance cameras over Cat cable
- POE ports support MDI/MDIX
- Support PoE power up to 15.4W(IEEE802.3af)/25.5W(IEEE802.3at) for PoE ports
- POE Lines: End-Span (12+,36-), Mid-Span (25+,78-)
- Support IEEE 802.3x flow control for Full-duplex Mode and back-pressure for Half-duplex Mode
- LED indicators for monitoring power, link, activity and speed
- Working Environment: Operating Temperature: 0 ° ~ 55 ° C; Storage Temperature: -40 ° ~ 85 ° C; Operating Humidity: 10% ~ 95%, non-condensing
- Forwarding Mode: Store-And-Forward
- MTBF: 100,000 hours

Applications

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

Product Specifications

Item	
POE	POE Port 8port POE 10/100M or 10/100/1000 Mbps
Uplink	Uplink 10/100/1000M Copper Port or 1000M Fiber Port
Power Type	Build In, Both 1/2+, 3/6- and 4/5+7/8-
Max. PoE Power Per Port	15.4W(IEEE802.3af) default, 25.5W(IEEE802.3at) optional
Network Protocols	IEEE 802.3, IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3af /IEEE 802.3at, IEEE 802.3x Flow control, IEEE 802.1q VLAN (optional)
LED Display	System: Power, PoE Maximum power Per port: Link, Activity, Speed, PoE active, PoE error
Transmission Distance	100/250meter for RJ45 ports; 0~120km for Fiber ports
Fiber Specification	Fiber Port: SC (default), FC/ST/LC(SFP) Wavelength/Distance: Dual Fiber 1310nm(2/20/40km); 1550nm(60/80/100/120km) Single Fiber 1310/1550nm(25/40km); 1490/1550nm(60/80/100/120km)

Ordering Information

Item	Description
AS200/10/FPU	10/100M 8POE+2RJ45
AS200/10/PU	10/100/1000M 8POE+2RJ45

Copyright @ Alpha Bridge Technologies Private Limited

This document is ABTPL Public Information. ABTPL reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.alphabridge.tech